

# IDENTIFICATION GUIDE FOR DRIVE SHAFTS



## LINE W / LINE W...E



Size	Cross and bearing kit	Inboard yoke	Profile pairing	STANDARD VERSION		OPTIONAL VERSION		
				Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
W 2100 W 100 E								
W 2200 W 200 E								
W 2300 W 300 E								
W 2400 W 400 E								
W 2500								
W 2600								

## LINE W WITH WIDE ANGLE JOINT ON ONE SIDE WWE / ON TWO SIDES WWZ



Size	Cross and bearing kit	Inboard yoke	Profile pairing	STANDARD VERSION		OPTIONAL VERSION		
				Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
W 2280								
W 2380								
W 2480								
W 2580								

## LINE P POWERDRIVE



Size	Cross and bearing kit	Inboard yoke	Profile pairing	STANDARD VERSION		OPTIONAL VERSION		
				Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
P 400								
P 500								
P 600								
P 700								
P 800								

## LINE P WITH WIDE ANGLE JOINT ON ONE SIDE PWE / ON TWO SIDES PWZ



Size	Cross and bearing kit	Inboard yoke	Profile pairing	STANDARD VERSION		OPTIONAL VERSION		
				Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
PW 480								
PW 580								
PW 675								

Dimensions for Guard type	SC	SD	PG
	SC/SD05 D = 47	SC/SD15 D = 58	PG25 D = 70
		PG30 D = 104	
		PG20 D = 85	

Connecting profiles	