

IDENTIFICATION GUIDE FOR DRIVE SHAFTS



LINE W / LINE W...E



	Cross and			STANDARD VERSION			OPTIONAL VERSION		
Size	bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones	
W 2100 W 100 E	55 10	63	23,5 3,4 00c(H) 0a	49 52,5 SD05	SD05	34,5 4 0v 1	5D15	74 165 SD15	
W 2200 W 200 E	61 20	70	34,5 4 0v 1	61 64,5 SD15	74 165 SD15	23,5 3,4 2,8 00c(H) 0a	57,5 49 52,5 SD05	62 132 SD05	
W 2300 W 300 E	75 21	84	34,5 4 0v 1	61 64,5 SD15	74 165 SD15	39,5 4,5 1b 2a	73 77 SD25	85 165 191 SD25	
W 2400 W 400 E	76 35	86	39,5 4,5 1b 2a	73 77 SD25	SD25	37 6 4,5 S4LH S5	90 80 80 SD25/1	85 165 191 SD25	
W 2500	89 36	100	4,5 S4 S5	73 77 SD25	SD25		90 80 80 SD25/1	85 165 191 SD25	
W 2600	104 26	120	47 57,5 4,5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	91,5 95,5 SD35	103 200 SD35	4,5 S4V S5	73 77 SD25	SD25	

LINE W WITH WIDE ANGLE JOINT ON ONE SIDE WWE / ON TWO SIDES WWZ





Cross and			STANDARD VERSION			OPTIONAL VERSION		
Size	bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
W 2280	61 20 22	70 22	34,5 4 2,7 1G	61 64,5 SD15	136 206 201 SDF15 SDF15	23,5 3,4 2,6 00cGA 0aG	57,5 49 52,5 SD05	142 142 SD05/SD15
W 2380	75 21 24	84 24	34,5 4 0vGA 1G	61 64,5 SD15	SDF15 SDF15	39,5 4,5 3,5 1bGA 2aG	73 77 SD25	SD15/SD25 SDF25 SDF25/20
W 2480	76 35 27	86 27	39,5 4,5 1bGA 2aG	73 77 SD25	SDF25/20 SDF25/20	6 4,5 S4LGA S5	90 80 80 SD25/1	SD25 SDF25/20 SDF25/20
W 2580	36 32	100 30	37 4,5 S4GA S5	73 77 SD25	SDF25/20 SDF25/20		90 80 80 SD25/1	SD25 SDF25/20 SDF25/20

LINE P POWERDRIVE



	Cross and		STANDARD VERSION			OPTIONAL VERSION		
Size	bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
P 400	76 35	86	39,5 4,5 1bH 2a	79 92 PG20	180 PG20	37 - 47- 6 4,5 S4LH S5	79 92 PG20	180 PG20
P 500	89 36	100	37 6 4,5 S4LH S5	79 92 PG20	180 PG20	37 4,5 S4V S5	79 92 PG20	180 PG20
P 600	104 26	120	47 57,5 4,5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	98 110 PG30	230 PG30			
P 700	118 27	138	47 57,5 4,5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	98 110 PG30	230 PG30			
P 800	135 28	155	60 x 55 (28)H	98 110 PG30	230 PG30V			

LINE P WITH WIDE ANGLE JOINT ON ONE SIDE PWE / ON TWO SIDES PWZ





Cross and			STANDARD VERSION			OPTIONAL VERSION		
Size	bearing kit	Inboard yoke	Profile pairing	Guard tubes	Guard cones	Profile pairing	Guard tubes	Guard cones
PW 480	76 35 27	86 33	39,5 4,5 1bGA 2aG	79 92 PG20	SDF25/20 SDF25/20	37 4,5 54LGA S5	79 92 PG20	SDF25/20 SDF25/20
PW 580	36 89 36 32	100 39	4,5 S4GA S5	79 92 PG20	SDF25/20 SDF25/20			
PW 675	104 26 36	115 39	4,5 S4GA S5	79 92 98 110 PG20 PG30	SDF25/20 SDF25/20	4,5 S5H S6H		

	SC SD		SC/SD05 D = 47	SC/SD15 D = 58	SC/SD25 D = 70	SC/SD35 D = 90
Dimensions	PG PG				PG25 D = 70	
for Guard type	PG	D11	PG20 D = 85	D D	PG30 D = 104	



